


型式_Model	消費電力 Power consumption	B部寸法 Dimension B	C部寸法 Dimension C	コネクタ Connector
LDL2-26X30SW2(A)	3.8W	38	26	SMR-03V-B ①:茶_Brown(+) ②:NC ③:青_Blue(-)
LDL2-50X30SW2(A)	7.6W	62	50	
LDL2-74X30SW2(A)	12W	86	74	
LDL2-98X30SW2(A)	16W	110	98	
LDL2-122X30SW2(A)	19W	134	122	
LDL2-146X30SW2(A)	23W	158	146	
LDL2-170X30SW2(A)	27W	182	170	
LDL2-194X30SW2(A)	31W	206	194	
LDL2-218X30SW2(A)	35W	230	218	
LDL2-242X30SW2(A)	38W	254	242	
LDL2-266X30SW2(A)	42W	278	266	
LDL2-290X30SW2(A)	46W	302	290	
LDL2-314X30SW2(A)	50W	326	314	
LDL2-338X30SW2(A)	53W	350	338	
LDL2-362X30SW2(A)	57W	374	362	
LDL2-386X30SW2(A)	61W	398	386	ELP-02V ①:茶_Brown(+) ②:青_Blue(-)
LDL2-410X30SW2(A)	65W	422	410	
LDL2-434X30SW2(A)	69W	446	434	
LDL2-458X30SW2(A)	72W	470	458	
LDL2-482X30SW2(A)	76W	494	482	
LDL2-506X30SW2(A)	80W	518	506	

入力電圧_Input Voltage : DC 24V
消費電力_Power Consumption : (表参照_Table reference)

UNIT:mm

000	DATE	DESCRIPTION	REVISED
REVISION			

ISSUE DATE	SCALE	APPROVED	NAME
2022/10/04	1:1	T.OSAWA	LDL2(A)(幅30シリーズ_width 30 series)
	SHEET SIZE	CHECKED	DRAWING NAME
	A3	Y.INOUE	外観図_outline
	PROJECTION	DESIGNED	DRAWING No.
		H.KITAGAWA	UA41501-G
		DRAWN	REVISION
		H.KITAGAWA	000



01/01